



# TRIPOD TURNSTILES SC-212-D

<b>Body</b>	: Outdoor water protected body, 1.2 mm 304 quality stainless steel.
<b>Hub</b>	: Aluminum casting, precision CNC machining.
<b>Mechanism</b>	: Aluminum casting, precision CNC machining, stainless steel impeller.
<b>Handles</b>	: 35x3 mm Aluminum polished handle (Opt. Stainless Steel)
<b>Dimensions</b>	: 470x435x950 mm, Arm:450 mm, ~38 kg
<b>Gauges</b>	: Standard on both feet. (Top cover optional)
<b>Energy and Power</b>	: 176-264 V AC 50-60 Hz / 24V DC Max: 20W
<b>Temperature</b>	: -20 / +60 °C - ( -40° with Opt. Heater )
<b>Working Mode</b>	: Two-way locked, one-way locked, one-way free, both directions free, adjustable trigger time.
<b>Features</b>	: Single contact, two-way switching, memory mode, service port, internal operation and transition
<b>Outputs</b>	: counters.Dry contact pass information for both directions separately, pc control port.
<b>Emergency</b>	: Free mode with emergency input, free mode when there is no power.
<b>Safety Status</b>	: With the safety status input, the turnstile goes into locked mode and never opens.
<b>Usage</b>	: 60 people per minute
<b>Option</b>	: Automatic falling arm, RF control card, counter, button, leak detection sensor.

