



TRIPOD TURNSTILES SC-272

| | |
|-------------------------|---|
| Body | : Outdoor water protected body, 1.2 mm 304 quality stainless steel. |
| Hub | : Aluminum casting, precision CNC machining. |
| Mechanism | : Aluminum casting, precision CNC machining, stainless steel impeller. |
| Handles | : 35x3 mm Aluminum polished handle (Opt. Stainless Steel) |
| Dimensions | : 300x450x270 mm, Arm: 450 mm, ~20 kg |
| Indicators | : tandard on both feet, (Top cover optional) |
| Energy and Power | : 76-264 V AC 50-60 Hz / 24V DC Max:10W |
| Temperature | : -20 / +60 °C - (-40° with Opt. Heater) |
| Working Mode | : Two-way locked, one-way locked, one-way free, both directions free, adjustable trigger time. |
| Features | : Single contact, two-way switching, memory mode, service port, internal operation and transition counters. |
| Outputs | : Dry contact pass information for both directions separately, pc control port. |
| Emergency | : Free mode with emergency input, free mode when there is no power. |
| Safety Status | : With the safety status input, the turnstile goes into locked mode and never opens. |
| Capacity | : 30 people per minute |
| Option | : Automatic falling arm, RF control card, counter, button, leak detection sensor. |

