



SWING GATE TURNSTILES SC-312-C



- Body** : 304 quality stainless steel cylindrical body, indoor use.
- Mechanism Wing** : Motor driven, solenoid locking, belt driven.
- Dimensions** : 10 mm laser cut plexiglass.
- Dimensions** : 230x230x1000 mm, Cylinder Diameter:168 mm Wing:500-800 mm, ~38 kg
- Indicators** : Two-color illuminated indicator on the wing is standard, it lights up red in standby and green when opening
- Opening Time** : 3 sec
- Energy and Power** : 176-264 V AC 50-60 Hz / 24V DC Max:30W
- Temperature** : -10 / +60 °C
- Working Mode** : Bidirectional motorized movement, automatic shutdown, deceleration mode.
- Features** : Operation mode selection, shutdown time setting, pc and service port, warning sound cancellation.
- Outputs** : Wing status information.
- Emergency** : With the emergency entrance, the turnstile opens in the desired direction, when there is no energy, it is opened by pushing it manually.
- Safety Status** : With the safety status input, the turnstile goes into locked mode and never opens.
- Usage Area** : Plazas, business centers, schools, municipalities, public institutions, factories.
- Option** : Your logo printed on the wing, RF control card, button, safety sensor, counter foot, reader foot.

