



# SWING GATE TURNSTILES SC-322-C

<b>Body</b>	: 304 quality stainless steel.
<b>Mechanism</b>	: Motor driven, solenoid locking, belt driven.
<b>Wing</b>	: 10 mm laser cut plexiglass.
<b>Dimensions</b>	: 220x320x1050 mm Wing: 500-800 mm, ~30 kg
<b>Opening Time</b>	: 3 sec
<b>Energy and Power</b>	: 176-264 V AC 50-60 Hz / 24V DC Max:30W
<b>Temperature</b>	: -10 / +60 °C
<b>Working Mode</b>	: Bidirectional motorized movement, automatic shutdown, deceleration mode.
<b>Features</b>	: Operation mode selection, shutdown time setting, pc and service port, warning sound cancellation.
<b>Outputs</b>	: Wing status information
<b>Emergency</b>	: With the emergency entrance, the turnstile opens in the desired direction, when there is no energy, it is opened by pushing it manually.
<b>Safety Status</b>	: With the safety status input, the turnstile goes into locked mode and never opens.
<b>Usage Area</b>	: Plazas, business centers, schools, municipalities, public institutions, factories.
<b>Option</b>	: Your logo printed on the wing, RF control card, button, safety sensor, counter foot, reader foot.

