



HALF HEIGHT TURNSTILES SC-432-Y-C-D



| | |
|-------------------------|---|
| Body | : 60x40 mm profile frame, 1.5 mm sheet steel. (Electrostatic powder coated or 304 stainless steel) |
| Coupling | : Aluminum casting, precision CNC machining. |
| Mechanism | : 10 mm laser cut steel sheet, precision CNC machining, stainless steel impeller. 3 lever mechanism. |
| Arms | : 10 mm laser cut plexiglass, 3 rows of arms screwed to the middle rotor. |
| Dimensions | : 2080x1150x1300 mm, Arm 550 mm, Transition range 580mm ~280 kg |
| Indicators | : Both directions on top panel. |
| Energy and Power | : 176-264 V AC 50-60 Hz / 24V DC Max: 50 W |
| Temperature | : -20 / +60 °C |
| Working Mode | : Two-way locked, one-way locked, one-way free, both directions free, adjustable trigger time. |
| Features | : Single contact, two-way switching, memory mode, service port, internal operation and transition counters. |
| Outputs | : Dry contact pass information separately for both directions, PC control port. |
| Emergency | : Free mode with emergency input, free mode when there is no power. |
| Safety Status | : With the safety status input, the turnstile goes into locked mode and never opens. |
| Capacity | : 40 people / minute |
| Option | : RF control card, counter, button, coin unit, reader unit, heater. |

