



# HALF HEIGHT TURNSTILES SC-442-Y



<b>Body</b>	: 40x40 mm profile frame, 1.5 mm sheet steel. (Electrostatic powder coated or 304 stainless steel)
<b>Coupling</b>	: Aluminum casting, precision CNC machining.
<b>Mechanism</b>	: 6 mm laser cut steel sheet, precision CNC machining, stainless steel impeller. 4 lever mechanism.
<b>Arms</b>	: 38x1.5 mm electrostatic powder painted or stainless steel, welded to the middle rotor, 6 rows of arms.
<b>Dimensions</b>	: 1380x1250x1500 mm, Arm 550 mm, Transition range 480mm ~175 kg
<b>Indicators</b>	: Both directions on top panel.
<b>Energy and Power</b>	: 176-264 V AC 50-60 Hz / 24V DC Max: 25W
<b>Temperature</b>	: -20 / +60 °C
<b>Working Mode</b>	: Two-way locked, one-way locked, one-way free, both directions free, adjustable trigger time.
<b>Features</b>	: Single contact, two-way switching, memory mode, service port, internal operation and transition counters.
<b>Outputs</b>	: Dry contact pass information separately for both directions, PC control port.
<b>Emergency</b>	: Free mode with emergency input, free mode when there is no power.
<b>Safety Status</b>	: With the safety status input, the turnstile goes into locked mode and never opens.
<b>Capacity</b>	: 20 people / minute
<b>Option</b>	: RF control card, counter, button, coin unit, reader unit, heater.

